

**TUNER**

FM/AM freq. range	87,5-108,0 MHz / 522-1620 kHz
FM/AM preset	18 x FM / 12 x AM
Usable sensitivity	1,6 µV
Channel separation	> 30 dB
Signal/noise level	> 60 dB

**USB/microSD**

USB system	USB 2.0
Max. current	1000 mA
File system	FAT 16/32, max. 32 GB
MP3 decoder	MPEG-1/2 AUDIO Layer-3
Number of channels	2-CH, stereo
Channel separation	> 76 dB
Signal/noise level	> 86 dB

**GENERAL PARAMETERS**

Car Voltage system	12 Volt Negative GND chassis
Operation Voltage	13,8 V DC (9 -16 V)
Type of display (16:9)	7" / 800x480 / TFT LCD
Video systems	PAL / NTSC
BT version	V2.1 + EDR / 5.0 m
BT profiles	A2DP, V1.2, AVRCP, V1.4
Channels of amplifier	4 CH
Power output	4 x 50 W max.
Speaker impedance	4 – 8 Ohm
Channel separation	> 80 dB
Signal/noise level	> 85 dB
Frequency range	20 - 20.000 Hz
Bass control	± 8 dB / 100 Hz
Treble control	± 8 dB / 10 kHz
Pre-amp output	2,0 Vrms max. (± 3 dB)
Video output	1,0 Vp-p (75 Ohm)
Fuse	F15A
T operation	0 °C ... +40 °C
Weight	0,78 kg
Chassis dimensions	178 x 101 x 70 mm / 2xDIN