

Box	2 way, bass-reflex
Pm	80 W
Pamp	60 W
Z	4 Ohm
f	50-20.000 Hz
THD	≤0,5 %
S/N	≥68 dB
∅Woofer/∅Coil	10" (250mm) / 1,5" (38mm)
Tweeter	1" (25mm) compression
File system	FAT16/32–MP3
USB system	USB 2.0
MP3/WMA decoder	MPEG-1/2 AUDIO Layer-3
FM range	87,6-108,0 MHz
MIC range	~50 m / <10mW
MIC frequency	VHF range

BT version	4.2 / 10 m max.
BT profiles	A2DP, AVRCP
Inputs, wired	FM/USB/microSD/AUX/MIC
Inputs, wireless	BT / 1 x MIC
AUX INPUT	∅3,5 mm
MIC INPUT	∅6,3 mm
Stand/∅	35 mm
Charging time	~3,5 h
Operation time	~8 h
Battery	Li-ion / 7,4 V / 1800 mAh
Adaptor PRI	230 V~ / 50 Hz
Adaptor SEC	9 V $\overline{=}$ / 1,5 A ⊖ ⊕
MIC batteries	2 x AA (1,5V)
Remote batterie	CR 2025 (3V)
Ta	0°C ... +35°C
Dimensions / Weight	~320 x 460 x 320 mm / ~4,8 kg