

PAX 42BT

PAX 42PRO (option)

Box	2 way, bass-reflex	2 way, bass-reflex
Pm / Pn	400 / 250 W	400 / 250 W
Pamp class A-B	250 W_{RMS}	-
Z	4 Ohm	8 Ohm
f	35-20.000 Hz	35-20.000 Hz
Spl (1W/1m)	96 dB	96 dB
S/N ratio	≥85 dB	-
∅ Woofer / ∅ Coil	15" (380mm)	15" (380mm)
Voice coil / Magnet	75 mm / 60 Oz	75 mm / 60 Oz
Tweeter diaphragm	1,75" titanium (44mm)	1,75" titanium (44mm)
Tweeter magnet	23 Oz	23 Oz
FM RADIO	87,6-108,0 MHz	-
BT VERSION	v5.0 / TWS	-
BT ERP	10m max.<1mW	-
USB / SD	FAT32 / 32GBmax.	-
FILE FORMATS	MP3-WMA-FLAC-WAV-APE	-
MIC INPUT	∅6,3 mm + XLR	-
LINE INPUT	2 x RCA + XLR	-
LINE OUTPUT	∅6,3 mm + XLR	-
SPEAKER IN	-	Speakon (1 x 8 Ohm)
SPEAKER OUT	Speakon (1 x 8 Ohm)	-
Stand / ∅	35 mm	35 mm
T_a	0°C...+35°C	0°C...+35°C
V / Hz / W	230V~ / 50Hz / 250W	-
Dimensions	~45 x 71 x 37 cm	~45 x 71 x 37 cm
kg	18,5 kg	16,5 kg