

TEST REPORT

COMMISSION REGULATION (EU) 2024/1103

implementing Directive 2009/125/EC of the European Parliament and of the Council as regards ecodesign requirements for local space heaters and separate related controls and repealing Commission Regulation (EU) 2015/1188

2024/90295 Corrigendum to Commission Regulation (EU) 2024/1103 of 18 April 2024 implementing Directive 2009/125/EC of the European Parliament and of the Council as regards ecodesign requirements for local space heaters and separate related controls and repealing Commission Regulation (EU) 2015/1188

| | |
|---|--|
| Report Reference No. | WST25C046578-P01 |
| Tested by (name + signature) | Jeson Fu/Project Engineer |
| Approved by (name + signature) | Michael Ling/Reviewer |
| Date of issue | 2025-04-03 |
| Total number of pages | 11 pages |
| Testing Laboratory | Shenzhen WST Testing Co., Ltd. |
| Address | 87 Guangshen Road, Baocheng 11st Zone, Xin'an Street, Bao'an, Shenzhen, Guangdong |
| Applicant's name | CIXI MAX ELECTRIC APPLIANCE CO.,LTD |
| Address | NO.411 XINSHEGNDONG ROAD, XINPU TOWN, CIXI, NINGBO, CHINA |
| Test specification: | |
| Test standard | Commission Regulation (EU) 2024/1103 |
| Non-standard test method | N/A |
| Test Report Form No. | |
| TRF Originator | WST |
| Master TRF | Dated 2025-03 |
| Test item description | Industrial fan heater |
| Trade Mark | NA |
| Manufacturer | CIXI MAX ELECTRIC APPLIANCE CO.,LTD NO.411 XINSHEGNDONG ROAD,XINPU TOWN, CIXI, NINGBO, CHINA |
| Model/Type reference | PTC2000S, PTC3000S, PTC2000, PTC2000R, PTC3000, TC3000R, PTC-20FC, PTC-30FC, PTC-2002, PTC-2003, PTC-2004, PTC-2005, PTC-2006, PTC-2007, PTC-2008, PTC-2009, PTC-2010, PTC-2011, PTC-2012, PTC-2013, PTC-2014, PTC-2015, PTC-2016, PTC-2017, PTC-2018, PTC-2019, PTC-2020, PTC2100, PTC2200, PTC2300, PTC2400, PTC2500, PTC2600, PTC2700, PTC2800, PTC2900 |
| Ratings | 220-240V~, 50-60Hz, 2000W, Class I |

| | |
|--|---------------------------|
| Test item particulars | Industrial fan heater |
| Classification of installation and use | Household indoor use only |
| Supply Connection..... | Type Y |
| Off mode | Yes |
| Standby mode..... | No |
| Possible test case verdicts: | |
| - test case does not apply to the test object | N/A |
| - test object does meet the requirement | P(Pass) |
| - test object does not meet the requirement | F(Fail) |
| Testing | |
| Date of receipt of test item..... | 2025-03-31 |
| Date (s) of performance of tests..... | 2025-03-31-2025-04-02 |
| Summary of testing: | |
| <p>From the result of our inspection and tests on the submitted sample(s), we conclude they comply with the requirements of COMMISSION REGULATION (EU) 2024/1103 implementing Directive 2009/125/EC of the European Parliament and of the Council as regards ecodesign requirements for local space heaters and separate related controls and repealing</p> <p>Commission Regulation (EU) 2024/90295 Corrigendum to Commission Regulation (EU) 2024/1103 of 18 April 2024 implementing Directive 2009/125/EC of the European Parliament and of the Council as regards ecodesign requirements for local space heaters and separate related controls and repealing Commission Regulation (EU) 2015/1188</p> | |
| General remarks: | |
| <p>The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.</p> <p>Throughout this report a comma is used as the decimal separator.</p> <p>Tests and measurements have been performed in accordance with EN 50564: 2011, EN 60675:1995+A1:1998 +A2:2018+A11:2019</p> <p>Determination of the test results includes consideration of measurement uncertainty from the test equipment and methods.</p> <p>The regulations on energy using products are undergoing a steady development. For testing and evaluating of the above mentioned products, the hereby applied standards and regulations are the most suitable and applicable test fundamentals for the time being. However it is possible, that these will be superseded by more product specific regulations as soon as they come into force, which might require other tests or evaluations.</p> <p>According to the regulation, the product information requirements from 1 July 2025, shall be given to a instruction manuals for installers and users, and free access websites of manufacturers, their authorised representatives and importers and the product packing. The information requirements of appended table with suggested value is just for reference, the value in table should be claimed by manufacturer.</p> | |

General product information:

The appliances covered by this report are Fan Heaters with mechanic thermostat for household use only.

Scope:

Appliances covered by Commission Regulation COMMISSION REGULATION (EU) 2024/1103 implementing Directive 2009/125/EC of the European Parliament and of the Council as regards ecodesign requirements for local space heaters and separate related controls and repealing Commission Regulation (EU) 2015/1188, 2024/90295 Corrigendum to Commission Regulation (EU) 2024/1103 of 18 April 2024 implementing Directive 2009/125/EC of the European Parliament and of the Council as regards ecodesign requirements for local space heaters and separate related controls and repealing Commission Regulation (EU) 2015/1188

Test result:

The measured data is less than the limit according 'Ecodesign requirements' of Annex II of the regulation (details see table 3 Requirements)

1. Description of the test subject

| Sample information | |
|---|-----------------------|
| Name of product | Industrial fan heater |
| Wall-mounted heater..... | No |
| Portable heater..... | Yes |
| Functions description | |
| Single stage heat output, no room temperature control..... | No |
| Two or more manual stages, no temperature control..... | No |
| With mechanic thermostat room temperature control..... | Yes |
| With electronic room temperature control..... | No |
| With electronic room temperature control plus day timer..... | No |
| With electronic room temperature control plus week timer..... | No |
| Other functions | |
| Room temperature control with presence detection..... | No |
| Room temperature control with open window detection..... | No |
| With distance control option function..... | No |
| With adaptive start control function..... | No |
| With working time limitation..... | No |
| With Black bulb sensor..... | No |
| With self-learning functionality..... | No |
| Control accuracy..... | No |

2. Requirements

2.1 Requirements for seasonal space heating energy efficiency:

2.1.1:

| Seasonal space heating energy efficiency (η_s) of | Measure | Requirement | Verdict |
|---|---------|---------------|---------|
| open fronted local space heaters and open to chimney local space heaters | -- | $\geq 40,3\%$ | NA |
| closed fronted open combustion local space heaters | -- | $\geq 63,6\%$ | NA |
| balanced flue local space heaters | -- | $\geq 63,6\%$ | NA |
| electric portable local space heaters | 44,7% | $\geq 44,7\%$ | P |
| electric fixed local space heaters with a nominal heat output above 250 W, except towel rails | -- | $\geq 47,5\%$ | NA |
| electric fixed local space heaters with a nominal heat output equal or below 250 W, except towel rails, | -- | $\geq 43,1\%$ | NA |
| electric storage local space heaters | -- | $\geq 47,3\%$ | NA |
| electric underfloor local space heaters | -- | $\geq 47,5\%$ | NA |
| electric visibly glowing radiant local space heaters with a nominal heat output above 1,2 kW, except electric visibly glowing radiant portable local space heaters | -- | $\geq 46,8\%$ | NA |
| electric visibly glowing radiant local space heaters with a nominal heat output equal or below 1,2 kW, except electric visibly glowing radiant portable local space heaters | -- | $\geq 40,5\%$ | NA |
| electric visibly glowing radiant portable local space heaters | -- | $\geq 39,5\%$ | NA |
| luminous local space heaters | -- | $\geq 90,0\%$ | NA |
| tube local space heaters | -- | $\geq 80,0\%$ | NA |
| towel rails with a nominal heat output above 250 W | -- | $\geq 46,0\%$ | NA |
| towel rails with a nominal heat output above 60 W and equal or below 250 W | -- | $\geq 42,1\%$ | NA |

2.1.2:

| Requirements | Remark | Verdict |
|--|--------|---------|
| Electric storage local space heaters shall be equipped with electronic heat charge control with room and/or outdoor temperature feedback and fan assisted heat output | -- | NA |
| Towel rails with a nominal heat output equal or below 60 W shall only be operable through a working time limitation with a maximum pre-set period of time no longer than 6 hours | -- | NA |
| Electric local space heaters placed on the market without control shall not be able to provide heat output without control | -- | NA |

2.2 Requirements for emissions (for liquid and gaseous fuel local space heaters):

| Emissions of nitrogen oxides (NO _x) by | Measure | Requirement ≤ | Verdict |
|---|---------|-----------------------------|---------|
| Open fronted local space heaters, open to chimney local space heaters, closed fronted open combustion local space heaters, balanced flue local space heaters and flueless local space heaters | -- | 120 mg/kWh _{input} | NA |
| Luminous local space heaters and tube local space heaters | -- | 180 mg/kWh _{input} | NA |

2.3 Requirements for low power modes:

| | Measure | Requirement ≤ | Verdict |
|--|---------|---------------|---------|
| Off mode | 0 W | 0,50 W | P |
| Off mode (from 2027-05-09) | -- | 0,30 W | NA |
| Standby mode With only reactivation function OR only reactivation function + mere indication of enabled reactivation function | -- | 0,50 W | NA |
| Standby mode With only information or status display OR only information or status display + reactivation function | -- | 1,00 W | NA |
| Networked standby | -- | 2,00 W | NA |
| Networked standby the communication between the heat generator and the control is wireless or through powerline carrier | -- | 3,00 W | NA |
| Idle mode | -- | 1,00 W | NA |
| Idle mode the idle mode depends on the input from a network connection to automatically provide heat to the room | -- | 3,00 W | NA |
| Supplementary information: | | | |

| Requirements | Remark | Verdict |
|---|--------|---------|
| If the standby mode includes the display of information or status, this function shall also be provided when the networked standby is provided. | -- | NA |

3 Evaluation

3.1 Calculation of seasonal space heating energy efficiency:

| | | |
|---|---|-----|
| The seasonal space heating energy efficiency of local space heaters is defined as: | | — |
| for gaseous fuel local space heaters and liquid fuel local space heaters, except commercial local space heaters | $\eta_S = \eta_{S,on}$ $= \eta_{th,nom} \cdot (0,75 + F(2) + F(3)) \cdot F(4) \cdot F(5)$ | N/A |
| for electric local space heaters | $\eta_{S,on} = \eta_{th,nom} \cdot (0,75 + F(2) + F(3)) \cdot F(4) \cdot F(5) = 85,0\%$ $\eta_S = \eta_{S,on} / CC = 44,7\%$ $F(2): 0,1$ $F(3): 0$ $F(4): 1$ $F(5): 1$ $\eta_{th,nom} = 100\%$ $CC = 1,9$ | P |
| for commercial local space heaters | $\eta_S = \eta_{S,on} - F(1) - F(4) - F(5)$ $\eta_{S,on} (\%) = \eta_{S,th} \cdot \eta_{S,RF} / 100$ $F(1):$ $F(4):$ $F(5):$ | N/A |
| a..For luminous local space heaters: | $\eta_{S,th} = 85,6 \%$ | N/A |
| b..For tube local space heaters: | $\eta_{S,th} = (0,15 \cdot \eta_{th,nom} + 0,85 \cdot \eta_{th,min}) - F_{env}$ | NA |
| thermal efficiency at nominal heat output (%) | $\eta_{th,nom}:$ | NA |
| thermal efficiency at minimum heat output (%) | $\eta_{th,min}:$ | NA |
| envelope losses of the heat generator (%) | $F_{env} : \text{see below table}$ | NA |
| c..For commercial local space heaters | $\eta_{S,RF} = \frac{(0,94 \cdot RF_S) + 0,19}{(0,46 \cdot RF_S) + 0,45} =$ | NA |
| - For all commercial local space heaters except tube systems | $RF_S = 0,15 \cdot RF_{nom} + 0,85 \cdot RF_{min} =$ | NA |
| radiant factor at nominal heat output (%) | $RF_{nom}:$ | NA |
| radiant factor at minimum heat output (%) | $RF_{min}:$ | NA |
| - For tube systems | $RF_S (\%) = \sum_{i=1}^n (0,15 \cdot RF_{nom,i} + 0,85 \cdot RF_{min,i}) \cdot \frac{P_{heater,i}}{P_{system}}$ | NA |
| radiant factor per tube segment at nominal heat output (%) | $RF_{nom,i}:$ | NA |
| radiant factor per tube segment at minimum heat output (%) | $RF_{min,i}:$ | NA |
| heat output per tube segment (kW) | $P_{heater,i}:$ | NA |
| heat output of the complete tube system (kW) | $P_{system}:$ | NA |
| Thermal transmittance of envelope (U) | F_{env} | — |
| $U \leq 0,5$ | 2,2 % | NA |
| $0,5 < U \leq 1,0$ | 2,4 % | NA |
| $1,0 < U \leq 1,4$ | 3,2 % | NA |
| $1,4 < U \leq 2,0$ | 3,6 % | NA |
| $U > 2,0$ | 6,0 % | NA |

3.2 Correction factor F(1)- F(5)**3.2.1: Correction factor F(1) for commercial local space heaters:**

| If the heat output control type of the products is: | F(1) [%] | With the following limits | Verdict |
|---|---|------------------------------|---------|
| Single stage | $F(1) = 5$ | | NA |
| Two stage | $F(1) = 5 - \left(2,5 \cdot \frac{P_{nom} - P_{min}}{0,3 \cdot P_{nom}} \right)$ | $2,5\% \leq F(1) \leq 5,0\%$ | NA |
| Modulating | $F(1) = 5 - \left(5,0 \cdot \frac{P_{nom} - P_{min}}{0,4 \cdot P_{nom}} \right)$ | $0\% \leq F(1) \leq 5,0\%$ | NA |

3.2.2 Correction factor F(2):

| If the product is equipped with (only one option may apply): | F(2) | | | | | | | Verdict |
|--|----------------------------------|-------|---------|-------------|-------------------------|--------------|---|---------|
| | for electric local space heaters | | | | | | for gaseous and liquid fuel local space heaters | |
| | Portable | Fixed | Storage | Under floor | Visibly glowing radiant | Towels rails | | |
| Single stage heat output, no room temperature control | 0 | 0 | 0 | 0 | 0 | 0 | 0 | NA |
| Two or more manual stages, no temperature control | 0,025 | 0 | 0 | 0 | 0,050 | 0,030 | 0,025 | NA |
| With mechanic thermostat room temperature control | 0,100 | 0,025 | 0,025 | 0,025 | 0,025 | 0,030 | 0,050 | P |
| With electronic room temperature control | 0,160 | 0,050 | 0,050 | 0,050 | 0,080 | 0,030 | 0,100 | NA |
| With electronic room temperature control plus day timer | 0,170 | 0,095 | 0,095 | 0,095 | 0,100 | 0,095 | 0,125 | NA |
| With electronic room temperature control plus week timer | 0,190 | 0,150 | 0,150 | 0,150 | 0,120 | 0,150 | 0,150 | NA |

3.2.3 Correction factor F(3):

| If the product is equipped with (multiple options may apply): | F(3) | | | | | | | Verdict |
|---|----------------------------------|-------|---------|------------|-------------------------|--------------|---|---------|
| | for electric local space heaters | | | | | | for gaseous and liquid fuel local space heaters | |
| | Portable | Fixed | Storage | Underfloor | Visibly glowing radiant | Towels rails | | |
| Room temperature control with presence detection | 0,005 | 0 | 0 | 0 | 0,040 | 0 | 0,025 | NA |
| Room temperature control with open window detection | 0,005 | 0,020 | 0,020 | 0,020 | 0,020 | 0,020 | 0,025 | NA |
| With distance control option | 0 | 0,020 | 0,020 | 0,020 | 0 | 0 | 0,025 | NA |
| With adaptive start control | 0,005 | 0,020 | 0,020 | 0,020 | 0 | 0,020 | 0 | NA |
| With working time limitation | 0,005 | 0 | 0 | 0 | 0,020 | 0,020 | 0 | NA |
| With black bulb sensor | 0 | 0 | 0 | 0 | 0,040 | 0 | 0 | NA |
| With self-learning functionality | 0 | 0,020 | 0,020 | 0,020 | 0,010 | 0,020 | 0,0125 | NA |
| Control accuracy with CA < 2 Kelvin and CSD < 2 Kelvin | 0,020 | 0,020 | 0,020 | 0,020 | 0 | 0,020 | 0,0125 | NA |

3.2.4 Correction factor F(4):

| | | |
|---|--|----|
| Gaseous and liquid fuel local space heaters except commercial local space heaters | $F(4) = \frac{1}{1 + \left(CC \cdot \frac{0,2 \cdot el_{max} + 0,8 \cdot el_{min}}{P_{nom}} \right)}$ | NA |
| electric power consumption at nominal heat output (kW) | el_{max} : | NA |
| electric power consumption at minimum heat output (kW) | el_{min} : | NA |
| nominal heat output (kW) | P_{nom} : | NA |
| Commercial local space heaters | $F(4)[\%] = CC \cdot \frac{0,15 \cdot el_{max} + 0,85 \cdot el_{min}}{P_{nom}} \cdot 100$ | NA |
| electric power consumption at nominal heat output (kW) | el_{max} : | NA |
| electric power consumption at minimum heat output (kW) | el_{min} : | NA |
| nominal heat output (kW) | P_{nom} : | NA |
| Electric local space heaters | $F(4) = 1$ | P |

3.2.5 Correction factor F(5):

| | | |
|---|---|----|
| Gaseous and liquid fuel local space heaters except commercial local space heaters | $F(5) = \frac{1}{1 + \left(0,5 \cdot \frac{P_{pilot}}{P_{nom}} \right)}$ | NA |
| pilot flame consumption (kW) | P_{pilot} : | NA |
| nominal heat output (kW) | P_{nom} : | NA |
| Commercial local space heaters | $F(5)[\%] = 4 \cdot \frac{P_{pilot}}{P_{nom}} \cdot 100$ | NA |
| pilot flame consumption (kW) | P_{pilot} : | NA |
| nominal heat output (kW) | P_{nom} : | NA |
| In case the product has no permanent pilot light (flame) P_{pilot} is 0 (Zero) | $P_{pilot} = 0$ | NA |
| Electric local space heaters | $F(5) = 1$ | P |

3.3 Correction Heat output evaluation

| TABLE 1: | heat output | |
|---|--------------------|-------------|
| No. | P measured (kW) | Note |
| PTC2000S, PTC3000S, PTC2000, PTC2000R, PTC3000, TC3000R, PTC-20FC, PTC-30FC, PTC-2002, PTC-2003, PTC-2004, PTC-2005, PTC-2006, PTC-2007, PTC-2008, PTC-2009, PTC-2010, PTC-2011, PTC-2012, PTC-2013, PTC-2014, PTC-2015, PTC-2016, PTC-2017, PTC-2018, PTC-2019, PTC-2020, PTC2100, PTC2200, PTC2300, PTC2400, PTC2500, PTC2600, PTC2700, PTC2800, PTC2900 | 2,0 | P_{nom} |
| | 1,0 | P_{min} |
| | 2,0 | $P_{max,c}$ |

3.4 Equipment used for measurements

| Equipment name | Model | Equipment ID | Last Calibration date | Calibration due date |
|----------------|------------|--------------|-----------------------|----------------------|
| Power meter | WT-310 | E0567 | 11/21/2024 | 11/20/2025 |
| Power Supply | AFC-31030T | E0132 | NA | NA |

4. Information requirements of Table 3

Table 3: Information requirements for electric local space heaters

| Contact details : | CIXI MAX ELECTRIC APPLIANCE CO.,LTD NO.411 XINSHEGNDONG ROAD,XINPU TOWN, CIXI, NINGBO, CHINA | | | | |
|---|---|-------|------|--|-------|
| Model identifier(s): PTC2000S, PTC3000S, PTC2000, PTC2000R, PTC3000, TC3000R, PTC-20FC, PTC-30FC, PTC-2002, PTC-2003, PTC-2004, PTC-2005, PTC-2006, PTC-2007, PTC-2008, PTC-2009, PTC-2010, PTC-2011, PTC-2012, PTC-2013, PTC-2014, PTC-2015, PTC-2016, PTC-2017, PTC-2018, PTC-2019, PTC-2020, PTC2100, PTC2200, PTC2300, PTC2400, PTC2500, PTC2600, PTC2700, PTC2800, PTC2900 | | | | | |
| Item | Sy mb ol | Value | unit | Item | unit |
| Heat output | | | | Type of heat output/room temperature control (select one) | |
| Nominal heat output | P_{nom} | 2,0 | kW | single stage heat output and no room temperature control | [no] |
| Minimum heat output (indicative) | P_{min} | 1,0 | kW | Two or more manual stages, no room temperature control | [no] |
| Maximum continuous heat output | $P_{max,c}$ | 2,0 | kW | with mechanic thermostat room temperature control | [Yes] |
| Power consumption | | | | with electronic room temperature control | |
| In off mode | P_o | 0 | W | electronic room temperature control plus day timer | [no] |
| In standby mode | P_{sm} | NA | W | electronic room temperature control plus week timer | [no] |
| In idle mode | | | | Other control options (multiple selections possible) | |
| In network standby | P_{nsm} | NA | W | room temperature control, with presence detection | [no] |
| Standby mode with display of information or status | | | no | room temperature control, with open window detection | [no] |
| Seasonal space heating energy efficiency in active mode | $\eta_{s,on}$ | 85,0 | % | distance control option | [no] |
| | | | | adaptive start control | [no] |
| | | | | working time limitation | [no] |
| | | | | black bulb sensor | [no] |
| | | | | self-learning functionality | [no] |
| | | | | Control accuracy | [no] |

Photo 1

Description: Overview



Photo 2

Description: Knob view

